

K58plus GNSS Receiver



K58plus GNSS Receiver

The advantage of lower price and better performance are depending on the reasonable and optimizing design to the subassemblies and components.

K58 plus combines the extraordinary GNSS signal tracking and processing technology of high-end equipment and the economy of an entry-level equipment.

Its superior flexibility and long endurance make it be a high-performance system to meet your diverse work needs on both simple and complex projects.

Key Features

- 440 Channels
- Enhanced endurance
- Long range radio Link
- WEB UI, WIFI, OTG
- Android Application
- Barrier-Free Measurement
- Advanced Multipath Reduction
- Provide solution using only GPS/GLONASS/BEIDOU/all the above

440 CHANNELS

Featuring a powerful 440 channels GNSS mainboard, K58 plus can track and process all the existed satellite constellations.

The tracking speed, signal reliability, positioning accuracy is greatly improved from old generation technology.

ENHANCED ENDURANCE

To have a longer working time in the field, dual batteries hot-swappable function is onboard with K58 plus. The typical battery life is 10 to 14 hours (RTK mode/ static mode).

ANDROID APPLICATION

KOLIDA SurvX field software provides an advanced, efficient, easy-to-use workflow to surveyors. Equipment configuration, coordinate system setting, data management, surveying programs are more intuitive and powerful than ordinary software.



LONG RANGE RADIO LINK

SDL-400 built-in radio can send signal as far as 7 km in urban area and 8 km in suburb. The maximum coverage area is up to 200 sq.km. It also features anti-interference capability, so K58 plus can work close to interference source.

BARRIER FREE MEASUREMENT

In difficult environment surveyor may lose connection with base station or VRS network. This unique feature can help user to continue working without interruption. 3 creative work modes to choose: Repeater/ Router/ Mobile Internet Reference Station.

Specifications

GNSS characteristics

■ KOLIDA Main Board

440 GNSS channels

- GPS L1C/A, L1C, L2C, L2E, L5, L2 C/A & P(y)
- GLONASS L1C/A, L2C/A, L2P, L3, P-code
- BeiDou B1, B2, B3
- Galileo GIOVE-A, GIOVE-B, E1, E5A, E5B
- SBAS L1C/A, L5

MSAS compatible, (WAAS/EGNOS/GAGAN/MSAS) Japan's Quasi-Zenith Satellite System L1C/A Ability to upgrade to be compatible with India's IRNSS system

■ **Initialization:** time <10s, reliability >99.99%

■ Supported data formats:

CMR+, CMRx, RTCM 2.1, RTCM 2.3, RTCM 3.0, RTCM 3.1, RTCM 3.2

■ Output data formats:

NMEA 0183, PJK plane coordinates, Binary code, Trimble GSOFF

Positioning Accuracy

Code differential GNSS positioning

- Horizontal: $\pm 0.25\text{m} + 1\text{ppm}$
- Vertical: $\pm 0.50\text{m} + 1\text{ppm}$

DGPS and SBAS accuracy

- Horizontal: 1m Vertical: 1.5m

Static and Fast Static accuracy

- Horizontal: $\pm 2.5\text{mm} + 0.1\text{ppm}$
- Vertical: $\pm 3.5\text{mm} + 0.5\text{ppm}$

Post-processing kinematic accuracy

- Horizontal: $\pm 8\text{mm} + 0.1\text{ppm}$
- Vertical: $\pm 15\text{mm} + 0.5\text{ppm}$

Real-time kinematic (RTK)

- Horizontal: $\pm 8\text{mm} + 1\text{ppm}$
- Vertical: $\pm 15\text{mm} + 1\text{ppm}$

Network RTK

- Horizontal: $\pm 8\text{mm} + 0.5\text{ppm}$
- Vertical: $\pm 15\text{mm} + 0.5\text{ppm}$

RTK initialization time

- 2~8s

Physical characteristics

Size

- 17.5 x 17.5 x 8.3 cm

Weight

- 1.33 kg (2 batteries included)

User interface

- Five Indicator lights (number of satellites, modem status, battery status)
- Two buttons
- Linux System

I/O interface

- 5PIN LEMO external power port+RS232

- 7PIN external USB(OTG)+Ethernet

- Bluetooth 2.1+EDR standard

- Bluetooth 4.0 standard, support android, ios connection, more than 10m Bluetooth connection range

Memory

- 8GB SSD internal storage 480 hours of continuous operation at 1Hz, L1 L2, 14 satellites minimum

- Support external USB storage (up to 32 GB)

- Automatic cycle storage

- Changeable record interval

- Up to 50Hz raw data collection

Operation

- Single-Base RTK, Network RTK, Single-Base DGPS, Network DGPS, Static

- Simultaneous storage of RAW data and RTK corrections output

- Start and stop of static survey measurement with a single button in the receiver

- Update rate: 10Hz, up to 50Hz

Environmental characteristics

- Operating temperature: -45°C to $+65^{\circ}\text{C}$

- Storage temperature: -55°C to $+85^{\circ}\text{C}$

- Humidity: 100% condensing

- IP67 waterproof, sealed against sand and dust

- Drop: 2m pole drop on concrete

- Environmental: Shock and Vibration

- Resistant (Rating: MIL STD 810 / 810F)

- The receiver can provide fixed solutions in harsh environments (urban areas, canopy environments, etc) using integrated filters

Power characteristics

- Two Li-Ion batteries, 7.4 V, 3400 mAh

- Battery life: >14h (static mode)
>10h (internal UHF base mode)
>12h (rover mode)

- External DC power: 9-28 V

UHF Radio characteristics

- Frequency Range 410-470MHz

- Channels & Frequency width:

- >50 CHANNELS (With 12.5KHz or 25KHz STEP)

- Protocol: TrimTalk450s, TrimMark3,

- SOUTH (KOLIDA)

- 1W/2W/3W switchable

- 10 km range, interference protected

- "Barrier-Free" Measurement Technology: Repeater/ Router/ CSD mode

WebUI

- Configure and monitor receiver by web server via Wi-Fi or USB cable

Cellular module characteristics

- WCDMA/CDMA2000/TDD-LTE/FDD-LTE 4G

- Compatible with 3G GPRS/EDGE

- Dual band GSM/GPRS modem (900, 1800 MHz) at least

Antenna

- ANTENNA GAIN 2.5 dBi

- Multipath Reduction FILTERS

- Elevation Mask

NFC

- Close range (shorter than 10cm) automatic pair between receiver and controller (need NFC chip in controller)

Wifi

- 802.11 b/g standard

- Hotspot: allow device to access in

- data link: broadcast differential data

Voice Guide

- intelligent voice technology provides status indication and operation guide

- Chinese, English, Korean, Russian, Portuguese, Spanish, Turkish and user define

Standard system components

- K58 plus Receiver

- Li-Ion battery

- Charger and adapter

- All-direction antenna

- Tape measure

- 30 cm pole extension

- 7-pin to OTG cable

- Engineering Star (Windows)

- Engineering Star (Android)

- 1 year warranty

Optional system components

- External Radio (410-470 MHz, 5-35W)

- Battery Case SA-6003

- Data collectors

- K720 (Windows)

- H3 plus (Android)

- T17 (Windows)

- X11 pro (Windows)

- Field software

- Field Genius (Windows)

- SurvX (Android)

- 1-2 year warranty extension

KOLIDA GEO OFFICE

Office Suite for Data Processing.



KOLIDA SurvX

Field Software for Android Device



KOLIDA Instrument Co., Ltd

7/F, No.39 SiCheng Road,
Guangzhou 510630, China

+86-20-22139033

export@kolidainstrument.com

KOLIDA
Professional's Choice